

Safety Data Sheet

LOCTITE 515 GASKET ELIMINATOR known as Loctite 515 50ML AU

Page 1 of 10

SDS No.: 153466

V001.4

Date of issue: 25.08.2020

respiratory tract irritation

Section 1. Identification of the substance/preparation and of the company/undertaking

Product name: LOCTITE 515 GASKET ELIMINATOR known as Loctite 515 50ML AU

Intended use: Anaerobic Adhesive

Supplier:

Henkel Australia Pty Ltd 135-141 Canterbury Road Kilsyth, Victoria, 3137 Australia

Phone: +61 (3) 9724 6444

Emergency information: 24 HOUR EMERGENCY CONTACT NUMBER: 1800 032 379

Section 2. Hazards identification

Classification of the substance or mixture

Hazardous according to the criteria of Safe Work Australia.

GHS Classification:

Hazard Class Hazard Category Target organ

Skin corrosion Category 1B Serious eye damage/eye irritation Category 1 Target Organ Systemic Toxicant -Category 3

Single exposure

Acute hazards to the aquatic

environment

Chronic hazards to the aquatic

environment

Category 2

Category 3

Hazard pictogram:



Signal word: Danger SDS No.: 153466

V001.4

LOCTITE 515 GASKET ELIMINATOR known as

Loctite 515 50ML AU

Hazard statement(s): H314 Causes severe skin burns and eye damage.

H335 May cause respiratory irritation.

H401 Toxic to aquatic life.

H412 Harmful to aquatic life with long lasting effects.

Precautionary Statement(s):

Prevention: P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P264 Wash hands thoroughly after handling. P271 Use only outdoors or in a well-ventilated area.

P273 Avoid release to the environment.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

Response: P301+P330+P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing.

Rinse skin with water [or shower].

P304+P340+P310 IF INHALED: Remove victim to fresh air and keep at rest in a position

comfortable for breathing. Immediately call a POISON CENTER or physician. P305+P351+P338+P315 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get immediate medical

advice/attention.

P363 Wash contaminated clothing before reuse.

Storage: P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P405 Store locked up.

Disposal: P501 Dispose of contents/container to an appropriate treatment and disposal facility in

accordance with applicable laws and regulations.

Dangerous Goods information:

Not classified as Dangerous Goods according to the criteria of the Australian Code for the Transport of Dangerous Goods by Road and Rail (ADG Code).

Section 3. Composition / information on ingredients

General chemical description: Mixture

Type of preparation: Anaerobic Sealant

Identity of ingredients:

Chemical ingredients	CAS-No.	Proportion
Acrylic acid	79-10-7	3- < 5 %
α, α-dimethylbenzyl hydroperoxide	80-15-9	1- < 3 %
2-Hydroxyethyl methacrylate	868-77-9	< 1 %
Acetic acid, 2-phenylhydrazide	114-83-0	< 1 %
non hazardous ingredients~		80- < 90 %

Section 4. First aid measures

Page 3 of 10

SDS No.: 153466

V001.4

LOCTITE 515 GASKET ELIMINATOR known as

Loctite 515 50ML AU

Ingestion: Do not induce vomiting.

Have victim rinse mouth thoroughly with water.

Seek medical advice.

Skin: In case of contact, immediately remove contaminated clothing and flush skin with copious

> amounts of water. Seek medical advice. Wash clothing before reuse.

Eyes: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.

Get immediate medical attention.

Inhalation: Move to fresh air in case of accidental inhalation of vapours.

Seek medical advice.

First Aid facilities: Eye wash and safety shower

Normal washroom facilities

Medical attention and special

treatment:

Treat symptomatically and supportively.

Section 5. Fire fighting measures

Suitable extinguishing media: Carbon dioxide, foam, powder

Decomposition products in case of

fire:

Thermal decomposition can lead to release of irritating gases and vapors. carbon monoxide

Carbon dioxide. Oxides of nitrogen. Oxides of sulfur.

Special protective equipment for

fire-fighters:

Wear full protective clothing.

Fire fighters should wear positive pressure self-contained breathing apparatus (SCBA).

Additional fire fighting advice: In case of fire, keep containers cool with water spray.

Collect contaminated fire fighting water separately. It must not enter drains.

Section 6. Accidental release measures

Personal precautions: Avoid skin and eye contact.

> Wear protective equipment. Ensure adequate ventilation.

Danger of slipping on spilled product. Keep unprotected persons away.

Environmental precautions: Waste disposal with the approval of the responsible local authority.

Do not discharge into surface water/ground water.

Clean-up methods: Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder,

sawdust).

Scrape up spilled material and place in a closed container for disposal.

LOCTITE 515 GASKET ELIMINATOR known as

Loctite 515 50ML AU

Section 7. Handling and storage

Precautions for safe handling: Use only in well-ventilated areas.

Avoid skin and eye contact.

Wear suitable protective clothing, safety glasses and gloves.

Conditions for safe storage: Store in original containers at 8-21°C (46.4-69.8°F) and do not return residual materials to

containers as contamination may reduce the shelf life of the bulk product.

Unsuitable materials with

product:

plastic

Section 8. Exposure controls / personal protection

National exposure standards:

In gredient [Regulated substance]	form of	TWA (ppm)	TWA	Peak Limit.	Peak Limit.	STEL (ppm)	STEL
	exposure		(mg/m3)	(ppm)	(mg/m3)		(mg/m3)
SILICA, AMORPHOUS: FUMED SILICA (RESPIRABLE DUST) 112945-52-5	Respirable dust.		2				
FUMED SILICA (RESPIRABLE DUST) 112945-52-5	Respirable dust.		2				
ACRYLIC ACID 79-10-7		2	5.9				

Engineering controls: Provide adequate local exhaust ventilation to maintain worker exposure below exposure

limits.

Eye protection: For eye protection, use tightly fitted safety goggles and a face-shield

Skin protection: Wear suitable protective clothing.

Recommended gloves include butyl rubber and neoprene.

Please note that in practice the working life of chemical resistant gloves may be considerably reduced as a result of many influencing factors (e.g. temperature). Suitable risk assessment should be carried out by the end user. If signs of wear and tear are noticed

then the gloves should be replaced.

Respiratory protection: If inhalation risk exists, wear a respirator or air supplied mask complying with the

requirements of AS/NZS 1715 and AS/NZS 1716.

Section 9. Physical and chemical properties

Appearance: purple, opaque

liquid Sharp

Odor: Sharp Specific gravity: 1.1

Boiling point: 150 °C (302 °F) **Flash point:** > 93.3 °C (>199.94 °F)

Vapor pressure: < 10 mm hg

(; 27 °C (80.6 °F))

Density: 1.1 g/cm3

Solubility in water: Slightly soluble (20 °C)

Viscosity (dynamic): 150,000 - 300,000 mPa.s

(BROOKFIELD WITH HELIPATH; Method: ;; LCT STM 10; Viscosity Brookfield)

VOC content: < 10 %

Page 5 of 10

SDS No.: 153466 V001.4

LOCTITE 515 GASKET ELIMINATOR known as Loctite 515 50ML AU

(2010/75/EC)

Section 10. Stability and reactivity

Stability: Stable under normal conditions of temperature and pressure.

Conditions to avoid: Avoid excessive heat and ignition sources.

Extremes of temperature.

Incompatible materials: Strong oxidizing agents.

Acids and bases. Reducing agents.

Hazardous decomposition

products:

Thermal decomposition can lead to release of irritating gases and vapors.

carbon monoxide Carbon dioxide. Oxides of sulfur. Oxides of nitrogen.

Hazardous polymerization: Will not occur.

Section 11. Toxicological information

Health Effects:

Ingestion: May cause mild gastrointestinal irritation with nausea, vomiting, diarrhea and abdominal pain.

Skin: Causes skin irritation.

Symptoms may include redness, edema, drying, defatting and cracking of the skin.

Eyes: Causes serious eye damage.

Contact with the eyes may cause moderate to severe eye injury. Eye contact may result in corneal injury. Symptoms may include discomfort or pain, excess blinking and tear production, with

marked redness and swelling of the conjunctiva.

Inhalation: Causes respiratory tract irritation.

Vapors may cause irritation of the nose, throat, and respiratory tract.

Acute toxicity:

Hazardous components	Value	Value	Route of	Exposure	Species	Method
CAS-No.	type		application	time		
Acrylic acid	LD50	1,500 mg/kg	oral		rat	BASF Test
79-10-7	LC50	> 5.1 mg/l	inhalation	4 h	rat	OECD Guideline 403 (Acute
	Acute	11 mg/l	inhalation			Inhalation Toxicity)
	toxicity	1,100 mg/kg	dermal			Expert judgement
	estimate					Expert judgement
	(ATE)					
	Acute					
	toxicity					
	estimate					
	(ATE)					
α, α-dimethylbenzyl	LD50	382 mg/kg	oral		rat	other guideline:
hydroperoxide	LD50	530 - 1,060			rat	other guideline:
80-15-9	Acute	mg/kg	dermal			Expert judgement
	toxicity	1,100 mg/kg	dermal			
	estimate					
2 11 1 1 1	(ATE)		,			
2-Hydroxyethyl	LD50	> 5,000 mg/kg	oral		rat	not specified
methacrylate	LD50	> 5,000 mg/kg			rabbit	not specified
868-77-9			dermal			121.1
Acetic acid, 2-	LD50	270 mg/kg	oral		rat	not specified
phenylhydrazide						
114-83-0						

LOCTITE 515 GASKET ELIMINATOR known as Loctite 515 50ML AU

Skin corrosion/irritation:

Hazardous components CAS-No.	Result	Exposure time	Species	Method
Acrylic acid 79-10-7	highly corrosive	3 min	rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
α, α-dimet hylbenzyl hydroperoxide 80-15-9	corrosive		rabbit	Draize Test

Serious eye damage/irritation:

Hazardous components CAS-No.	Result	Exposure time	Species	Method
Acrylic acid 79-10-7	corrosive	21 d	rabbit	BASF Test
2-Hydroxyethyl methacrylate 868-77-9	irritating		rabbit	Draize Test

Respiratory or skin sensitization:

Hazardous components	Result	Test type	Species	Method
CAS-No.				
Acrylic acid	not sensitising	Skin	guinea pig	not specified
79-10-7		painting		
		test		

Germ cell mutagenicity:

Hazardous components CAS-No.	Result	Type of study/ Route of administration	Metabolic activation / Exposure time	Species	Method
Acrylic acid 79-10-7	negative negative	mammalian cell gene mutation assay DNA damage and repair assay, unscheduled DNA synthesis in mammalian cells in vitro	with and without without		OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test) OECD Guideline 482 (Genetic Toxicology: DNA Damage and Repair, Unscheduled DNA Synthesis in Mammalian Cells In Vitro)
Acrylic acid 79-10-7	negative	oral: gavage		rat	OECD Guideline 475 (Mammalian Bone Marrow Chromosome Aberration Test)
α, α-dimethylbenzyl hydroperoxide 80-15-9	positive	bacterial reverse mutation assay (e.g Ames test)	without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
α, α-dimethylbenzyl hydroperoxide 80-15-9	negative	dermal		mouse	not specified
2-Hydroxyethyl met hacrylate 868-77-9	negative positive negative negative	bacterial reverse mutation assay (e.g Ames test) in vitro mammalian chromosome aberration test mammalian cell gene mutation assay bacterial reverse mutation assay (e.g Ames test)	with and without with and without with and without with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay) OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test) OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test) OECD Guideline 472 (Genetic Toxicology: Escherichia coli, Reverse Mutation Assay)
2-Hydroxyethyl methacrylate 868-77-9	negative	oral: gavage		rat	OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test)

Page 7 of 10

SDS No.: 153466 V001.4

LOCTITE 515 GASKET ELIMINATOR known as

Loctite 515 50ML AU

Repeated dose toxicity:

Hazardous components CAS-No.	Result	Route of application	Exposure time / Frequency of treatment	Species	Method
α, α-dimethylbenzyl hydroperoxide 80-15-9		inhalation: aerosol	6 h/d5 d/w	rat	not specified
2-Hydroxyethyl methacrylate 868-77-9	NOAEL=100 mg/kg	oral: gavage	once daily	rat	OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)

Section 12. Ecological information

LOCTITE 515 GASKET ELIMINATOR known as

Loctite 515 50ML AU

General ecological information: Do not empty into drains / surface water / ground water.

Ecotoxicity: Toxic to aquatic life with long lasting effects.

Toxicity:

Hazardous components CAS-No.	Value type	Value	Acute Toxicity Study	Exposure time	Species	Method
Acrylic acid	LC50	27 mg/l	Fish	96 h	Salmo gairdneri (new name:	EPA OTS
79-10-7					Oncorhynchus mykiss)	797.1400 (Fish
						Acute Toxicity Test)
Acrylic acid	EC50	95 mg/l	Daphnia	48 h	Daphnia magna	EPA OTS
79-10-7		7 8 -				797.1300 (Aquatic
						Invertebrate Acute
						Toxicity Test, Freshwater
						Daphnids)
Acrylic acid	EC10	0.03 mg/l	Algae	72 h	Scenedesmus subspicatus (new	EU Method C.3
79-10-7					name: Desmodesmus	(Algal Inhibition
Acrylic acid	EC50	0.13 mg/l	Algae	72 h	subspicatus) Scenedesmus subspicatus (new	test) EU Method C.3
79-10-7	LC30	0.13 mg1	riigae	/ 2 11	name: Desmodesmus	(Algal Inhibition
					subspicatus)	test)
Acrylic acid 79-10-7	EC20	900 mg/l	Bacteria	30 min	activated sludge, domestic	ISO 8192 (Test for Inhibition of
/9-10-/						Oxygen
						Consumption by
]	1.050	2.0 //	F" 1	0.6.1	0 1 1 1	Activated Sludge)
α, α-dimethylbenzyl hydroperoxide	LC50	3.9 mg/l	Fish	96 h	Oncorhynchus mykiss	OECD Guideline 203 (Fish, Acute
80-15-9						Toxicity Test)
α, α-dimethylbenzyl	EC50	18 mg/l	Daphnia	48 h	Daphnia magna	OECD Guideline
hydroperoxide 80-15-9						202 (Daphnia sp. Acute
80-13-9						Immobilisation
						Test)
α, α-dimethylbenzyl	ErC50	3.1 mg/l	Algae	72 h	Pseudokirchneriella subcapitata	
hydroperoxide 80-15-9						201 (Alga, Growth Inhibition Test)
α , α -dimethylbenzyl	EC10	70 mg/l	Bacteria	30 min		not specified
hydroperoxide		C				1
80-15-9	LC50	> 100 m a/l	Fish	96 h	Ouvering latings	OECD Guideline
2-Hydroxyethyl methacrylate 868-77-9	LC30	> 100 mg/l	FISH	90 11	Oryzias latipes	203 (Fish, Acute
						Toxicity Test)
2-Hydroxyethyl methacrylate	EC50	380 mg/l	Daphnia	48 h	Daphnia magna	OECD Guideline
868-77-9						202 (Daphnia sp. Acute
						Immobilisation
						Test)
2-Hydroxyethyl methacrylate 868-77-9	EC50	836 mg/l	Algae	72 h	Selenastrum capricornutum (newname: Pseudokirchneriella	OECD Guideline
000-77-9					subcapitata)	Inhibition Test)
2-Hydroxyethyl methacrylate	NOEC	400 mg/l	Algae	72 h	Selenastrum capricornutum	OECD Guideline
868-77-9					(new name: Pseudokirchneriella	
2-Hydroxyethyl methacrylate	EC0	> 3,000 mg/l	Bacteria	16 h	subcapitata) Pseudomonas fluorescens	Inhibition Test) other guideline:
868-77-9	LCU	> 5,000 mg/1	Bucteria	1011	1 seudomonus muorescens	orner guidenne.

$\label{persistence} \textbf{Persistence and degradability:}$

Hazardous components	Result	Route of	Degradability	Method
CAS-No.		application		

LOCTITE 515 GASKET ELIMINATOR known as Loctite 515 50ML AU

Acrylic acid 79-10-7	inherently biodegradable	aerobic	100 %	OECD Guideline 302 B (Inherent biodegradability: Zahn- Wellens/EMPA Test)
Acrylic acid 79-10-7	readily biodegradable	aerobic	81 %	OECD Guideline 301 D (Ready Biodegradability: Closed Bottle Test)
α, α-dimethylbenzyl hydroperoxide 80-15-9		no data	0 %	OECD Guideline 301 B (Ready Biodegradability: CO2 Evolution Test)
2-Hydroxyethyl methacrylate 868-77-9	readily biodegradable	aerobic	92 - 100 %	OECD Guideline 301 C (Ready Biodegradability: Modified MITI Test (1))

Bioaccumulative potential / Mobility in soil:

Hazardous components CAS-No.	LogPow	Bioconcentration factor (BCF)	Exposure time	Species	Temperature	Method
Acrylic acid 79-10-7		3.16				QSAR (Quantitative Structure Activity Relationship)
Acrylic acid 79-10-7	0.46				25 °C	OECD Guideline 107 (Partition Coefficient (noctanol / water), Shake Flask Method)
α, α-dimethylbenzyl hydroperoxide 80-15-9		9.1		calculation		OECD Guideline 305 (Bioconcentration: Flow- through Fish Test)
α, α-dimethylbenzyl hydroperoxide 80-15-9	2.16					not specified
2-Hydroxyethyl methacrylate 868-77-9	0.42				25 °C	OECD Guideline 107 (Partition Coefficient (noctanol / water), Shake Flask Method)
Acetic acid, 2- phenylhydrazide 114-83-0	0.74					not specified

Section 13. Disposal considerations

Waste disposal of product: Dispose of in accordance with local and national regulations.

Disposal for uncleaned package: After use, tubes, cartons and bottles containing residual product should be disposed of as

chemically contaminated waste in an authorised legal land fill site or incinerated.

Disposal must be made according to official regulations.

Section 14. Transport information

Road and Rail Transport:

Dangerous Goods information: Not classified as Dangerous Goods according to the criteria of the

Australian Code for the Transport of Dangerous Goods by Road and

Rail (ADG Code).

 $\label{lem:marine transport IMDG:} \begin{picture}(100,0) \put(0,0){\line(1,0){100}} \put(0,0){\li$

Not dangerous goods

Air transport IATA:

Not dangerous goods

Page 10 of 10

SDS No.: 153466 V001.4

LOCTITE 515 GASKET ELIMINATOR known as

Loctite 515 50ML AU

Section 15. Regulatory information

SUSMP Poisons Schedule

None

Section 16. Other information

Abbreviations/acronyms: ADGC - Australian Dangerous Goods Code

GHS: Globally Harmonized System CAS: Chemical Abstracts Service

OECD: Organization for Economic Cooperation and Development

LD 50: Lethal Dose 50%

LC 50: Lethal Concentration 50%

IMDG: International Maritime Dangerous Goods code

IATA-DGR: International Air Transport Association – Dangerous Goods Regulations

STEL - Short term exposure limit TWA - Time weighted average

Reason for issue: Reviewed SDS. Reissued with new date. involved chapters: 2,3,4,6,9,12,15,16

Date of previous issue: 21.09.2015

Disclaimer:

The percentage weight (% w/w) of ingredients is not to be taken as a specification guaranteed by Henkel Australia Pty. Limited, but only as an approximate guide to the content of hazardous ingredients in the material. The information contained herein does not constitute a guarantee by Henkel Australia Pty. Limited concerning the properties of the material.

The information contained in the Safety Data Sheet is offered in good faith and has been developed from what is believed to be accurate and reliable sources. The information is offered without warranty, representation, inducement or licence and Henkel Australia Pty. Limited assumes no legal responsibility for reliance upon same. Henkel Australia Pty. Limited disclaims any liability for loss, injury or damage incurred in connection with the use of the material or its associated Safety Data Sheet.

This information is not to be construed as a representation that the material is suitable for any particular purpose or use except those conditions and warranties implied by either Commonwealth or State statutes. Customers are encouraged to make their own enquiries as to the material's characteristics and, where appropriate, to conduct their own tests in the specific context of the material's intended use.

No warranty or representation of any kind is given with respect to the substantive or export laws of any other jurisdiction or country. Please confirm that the information provided herein conforms to the substantive export or other law of any other jurisdiction prior to export. Please contact Henkel Product Safety and Regulatory Affairs for additional assistance.