



PRODUCT INFORMATION

JUNE 2018 Update



14512 Quick Release Grease Gun Coupler

**Struggling with your grease gun coupler when greasing your equipment?
With the Alemlube 14512 Quick Release Grease Gun Coupler, struggle no more.**

The 14512 is a game changing patented lock-on grease gun coupler with a lever action and sliding sleeve that securely locks the coupler onto a grease nipple creating a leak proof seal.

Hands-free greasing is now a reality!

The 14512 quick release grease gun coupler is locked onto a grease nipple simply by depressing the trigger, attaching and releasing the trigger for a tight fit. No hands are needed to align the coupler or keep it on the nipple.

Leak proof greasing - even at extreme angles

Once the 14512 is attached, greasing can be performed at pressures of up to 10,000psi (690bar) - and can be forced to extreme angles on the grease nipple without leaking.

Activate the trigger to disengage - easy release

Simply pressing the trigger releases the coupler from the grease nipple.



PRODUCT SPECIFICATIONS, FEATURES AND BENEFITS

Works with all grease gun types - pneumatic, manual and battery

1/8" BSP (f) thread

Maximum working pressure of 10,000psi (690 bar)

Fits all metric and SAE specification grease nipples

4 hardened spring steel jaws resilient under high pressure

Durable nitrile rubber seal for longevity under high pressure

Sliding sleeve locks the quick release coupler onto the nipple

Suitable for high pressure, heavy duty greasing applications

No need to hold while greasing

Lock-on and free up both hands to operate your grease gun

Easy clip-off, regardless of pressure build up in the line

90mm in length

Weighs only 100g

Also suitable for underground coal mine applications

ORDERING INFORMATION

A14512 Quick release grease gun coupler

